



Floor & Porch Enamel



Inside or out, PPG Floor & Porch Enamels are ideal for high-traffic areas such as basement floors, patios, decks, steps and porches. For use on properly primed concrete, wood and metal, our advanced formulas apply easily and clean up with soap and water. Available in satin and gloss finishes, PPG Floor & Porch Enamels come in your choice of ready-mix colors, as well as hundreds of custom colors from the Voice of Color® design collection.



**100% ACRYLIC
LATEX FORMULA
SATIN FINISH**

Product	Code	Sizes
White/Pastel Base	3-510	1s, 5s
Midtone Base	3-515	1s
Deeptone Base	3-516	1s
Ultra Deep Base	3-540	1s
Dixie Gray	3-517	1s
Pewter Gray	3-518	1s
Walnut	3-523	1s
Tile Red	3-524	1s



**WATER-BORNE
ALKYD FORMULA
GLOSS FINISH**

Product	Code	Sizes
White/Pastel Base	3-610	1s
Midtone Base	3-620	1s
Deeptone Base	3-630	1s
Dixie Gray	3-617	1s
Walnut	3-623	1s
Tile Red	3-624	1s



100% ACRYLIC LATEX FORMULA SATIN FINISH




- Advanced urethane-fortified formula dries to a tough satin finish that stands up to wear and tear better than ordinary latex floor paints
- Easily cleans up with warm, soapy water
- Excellent adhesion to multiple surfaces
- Fast-drying and scuff resistant
- Available in ready-mix colors and the nearly 2,000 custom colors from the Voice of Color® design collection
- Can earn LEED NC Version 2.2 and 3.0 Credits (with the exception of 3-540)

BETTER ABRASION RESISTANCE

The PPG product withstood 400 cycles without showing any breakthrough of the film. This means better resistance to abrasion so you can walk on your surface with confidence.



PPG 100% Acrylic Latex
Dixie Gray (3-517)



Leading Competitor Acrylic
Gloss Ready Mix Gray

Test paints are applied, by drawbar, to a black plastic panel (Leneta Scrub Panel P-121-10N) using 7 mil gap application bar and cure 7 days under the conditions specified. ASTM method D 2486 were used with the following exceptions: 1) There shall be no shim applied to the back of the panel, 2) the scrub media shall be an 80% VIM detergent in distilled water applied dropwise from a burette to the surface under test at a rate of 8-10 drops per minute, and 3) the test will be performed continuously, without interruption, and without the addition of extra solution or water, to the conclusion of the specified number of cycles.

WATER-BORNE ALKYD FORMULA GLOSS FINISH




- High-gloss enamel provides bright, protective finish
- Performance of an alkyd with easy water clean up
- Excellent adhesion to multiple surfaces
- Scuff and abrasion resistant
- Available in ready-mix colors and more than 1,500 custom colors from the Voice of Color® design collection
- VOC compliant in all regulated areas
- Can earn LEED NC Version 2.2 and 3.0 Credits

SMOOTHER FLOW, LESS BRUSH STROKES

The PPG product offers better flow and leveling so brush strokes in corners or around posts or railings will be virtually unnoticeable.



PPG WB Alkyd
Dixie Gray (3-617)



Leading Competitor
WB Alkyd Ready Mix Gray

Test paints are applied to Leneta Form WB – Plain White Chart using a grooved Leveling Test Bar designed to lay down a wet film with parallel ridges. Paints are allowed to dry overnight in a horizontal position. An oblique light source is used to view the cured test paints. The dry draw-downs are placed perpendicular to the direction of the light.



PPG Architectural Coatings, One PPG Place, Pittsburgh, PA 15272
Technical Services: 1-800-441-9695, Architect/Specifier: 1-888-PPG-IDEA
www.ppgpittsburghpaints.com www.ppgporterpaints.com