



SANDING SEALER

— PREMIUM —
INTERIOR



Prepares Wood for a Smooth, Even Topcoat



OIL BASED SANDING SEALER

- Fast drying
- Sands easily
- For use on wood floors

WATER BASED SANDING SEALER

- Fast drying
- Sands easily
- For use on wood floors
- Soap and water cleanup

OLYMPIC® PREMIUM INTERIOR SANDING SEALER



PRODUCT OVERVIEW

Olympic Premium Interior Sanding Sealers are available in both water-based and oil-based formulas. Both products are formulated to create an ultra smooth surface prior to the application of a finish coat. These products will allow you to achieve professional looking results; they are fast drying, easy to sand and allow for multiple applications in one day. Olympic Premium Sanding Sealers are specially designed for use on stained or unfinished interior wood surfaces including floors, doors, trim, furniture, cabinets and paneling.

APPLICATION TECHNIQUES

Apply Olympic Premium Water Based Sanding Sealer with a synthetic brush or foam applicator pad. Apply Olympic Premium Oil Based Sanding Sealer with a natural bristle brush.

Always sand with the grain of the wood. For hard woods, such as oak and maple, begin sanding with 100 grit sandpaper, then proceed to 150 grit sandpaper, and finish with 200 grit or finer sandpaper. For softwoods, such as pine, begin sanding with 150 grit sandpaper and finish with 200 grit sandpaper. Clean the sanding dust from the surface using a tack cloth or vacuum cleaner.

ADDITIONAL INFORMATION

Water-Based:

Dry time: Allow a minimum of 2 hours before sanding

Clean up: Soap and water

Coverage: Up to 400-500 sq. ft. per gallon
(100-125 sq. ft. per quart)

For use on: Floors, doors, trim, furniture, cabinets and paneling

Oil-Based:

Dry time: Allow a minimum of 2 hours before sanding

Clean up: Mineral spirits or paint thinner

Coverage: Up to 500-700 sq. ft. per gallon
(125-175 sq. ft. per quart)

For use on: Floors, doors, trim, furniture, cabinets and paneling

PRODUCTS

Product	Code	Available Size
Water Based	41061	Quart & Gallon
Oil Based	41060	Quart & Gallon

COMMONLY ASKED QUESTIONS

When should I apply a sanding sealer? Use a sanding sealer when you want an ultra smooth surface after staining and before applying a finish coat. It can be used on all types of bare wood as well as stained wood. Sanding sealers help fill small pits in the wood's surface to help you achieve a uniform, seamless end result. Make sure your wood is dust free before sealing.

How many coats are required? Usually one or two coats are recommended. Be sure to lightly sand and remove all sanding dust in between coats.

Can Olympic Premium Water Based and Oil Based Sanding Sealers be used over all types of stains? Yes, you can apply a sanding sealer over any of the Olympic Premium Wood Stains, Fast Dry Stains and Gel Stains as well as on bare wood. Always make sure the stain is fully dry according to label directions before applying a sanding sealer.

Can Olympic Premium Water Based and Oil Based Sanding Sealers be used under all types of topcoats? Sanding sealers work well under most oil based and water based topcoats. However, the Olympic Premium Oil Based Sanding Sealer is not recommended under the Olympic Premium Oil Based Polyurethane. Because the Oil Based Polyurethane is self-sealing, application of the Oil Based Sanding Sealer may cause adhesion issues when the two products are used together.



VISIT OUR WEBSITE AT WWW.OLYMPIC.COM

Olympic is a registered trademark of PPG Architectural Finishes, Inc.
PPG Architectural Finishes, Inc., One PPG Place, Pittsburgh, PA 15272